



## Prison version

Convotherm 4 easyTouch<sup>®</sup> and easyDial<sup>™</sup>

# Convotherm 4 Designed around you

Listening carefully to you, the customer, we have developed the Convotherm 4 around your needs in the kitchen. The two control-panel designs - easyTouch® and easyDial™ - give you the degree of control you require: from full automation to maximum customisation. The aim of both is to deliver the functions you need in a user-friendly design.



► **Redefined: Clear design meets functionality**

The new Convotherm 4 design is also ideal for “front-of-house cooking”. Developed in strict adherence to the principle of “form follows function”, clear aesthetics are combined with a new dimension in intuitive operation and straightforward servicing.

► **The new standard in flexible, reliable cleaning**

ConvoClean+™ and ConvoClean™ have been developed to deliver maximum flexibility with minimum consumption. Strictly fully automatic: avoids any contact with chemicals when starting the cleaning process. With a new range of operating functions and a single dosage option, these cleaning systems can satisfy absolutely every user profile.

► **Your cooking results in focus**

The legend lives on! The Advanced Closed System+ (ACS+) offers perfection in the 3<sup>rd</sup> generation. It delivers the ultimate in even cooking and baking, with results always optimised to your requirements.

► **Lower operating costs while helping the environment.**

Every watt and litre count. The Convotherm 4 represents a new class of energy efficiency and water consumption compared with the previous P3 model. Using hydroelectric power and heat produced from biomass for production at our Eglfing site sends the clear message that for us, sustainability starts back at the factory.

# How the prison version can help you

The Convotherm 4 prison version\* contains extra features to meet your specific requirements. These features are designed to prevent wilful damage and misuse of appliances and accessories and ensure food is prepared in a secure environment.



The lockable\*\* control-panel cover prevents unauthorized use of the appliance. For instance, people cannot start, pause or stop cooking processes without permission. Only authorised personnel can start fully automatic cleaning, and permission is needed to start or intervene in the cleaning process.



The ergonomic USB port provides secure access to HACCP data, with downloads restricted to authorised personnel. Cooking profile uploads and software updates can also be performed securely via this port.



The lockable\*\* appliance door prevents anyone from placing foreign objects in the oven or removing food from the chamber, and avoids any interruptions in the cooking process by opening the door. The closed appliance door can be locked in two positions: either fully closed or allowing opening only as far as the steam release position.



For appliances of size 12.20, 20.10 and 20.20, the loading trolley has a fixed and specially coated handle.

The door window and sealing pane are made of specially toughened safety glass for extra-high strength. (a 50 mm square crumbles into > 240 fragments. The standard number for TSG is 60 fragments.)

Further modifications are possible on request.



\* incompatible with the following options: external core temperature probe/sous-vide sensor, ConvoSmoke and ConvoGrill

\*\* using padlock. Padlock not supplied.

# Convotherm 4 combi ovens

## Designed around you

	6.10	6.20	10.10	10.20
<b>Dimensions, right-hinged door</b> (WxDxH) in mm	875 x 792 x 786	1120 x 992 x 786	875 x 792 x 1058	1120 x 992 x 1058
<b>Dimensions, disappearing door</b> (WxDxH) in mm	922 x 792 x 786	1167 x 992 x 786	922 x 792 x 1058	1167 x 992 x 1058
<b>GN</b>	6+1 x 1/1	12+2 x 1/1, 6+1 x 2/1	10+1 x 1/1	10+1 x 2/1
<b>Rated power consumption</b> <b>Electric Injection/Spritzer, Electric Boiler</b> (3N~ 400V 50/60Hz (3/N/PE))	11.0 kW	19.5 kW	19.5 kW	33.7 kW
<b>Heat output</b> (natural gas 2H (E))	11.0 kW	21.0 kW	21.0 kW	31.0 kW

	12.20	20.10	20.20
<b>Dimensions, right-hinged door</b> (WxDxH) in mm	1135 x 1020 x 1406	890 x 820 x 1942	1135 x 1020 x 1942
<b>Dimensions, disappearing door</b> (WxDxH) in mm	1182 x 1020 x 1406	937 x 820 x 1942	1182 x 1020 x 1942
<b>GN</b>	24 x 1/1, 12 x 2/1	20 x 1/1	40 x 1/1, 20 x 2/1
<b>Rated power consumption</b> <b>Electric Injection/Spritzer, Electric Boiler</b> (3N~ 400V 50/60Hz (3/N/PE))	33.7 kW	38.9 kW	67.3 kW
<b>Heat output</b> (natural gas 2H (E))	31.0 kW	42.0 kW	62.0 kW



Welbilt offers fully-integrated kitchen systems and our products are backed by KitchenCare® aftermarket parts and service. Welbilt's portfolio of award-winning brands includes **Cleveland™**, **Convotherm®**, **Delfield®**, **fitkitchenSM**, **Frymaster®**, **Garland®**, **Kolpak®**, **Lincoln™**, **Manitowoc®**, **Merco®**, **Merrychef®** and **Multiplex®**.

*Bringing innovation to the table • [welbilt.com](http://welbilt.com)*